

Pellacoat

Description: Pellacoat is a molasses based pellet de-duster. It is a blend of molasses (a by-product consisting of the syrupy residue collected during the manufacture or refining of sugar from sugar cane/beet), condensed molasses solubles (a high protein by-product from the fermentation of molasses in the production of alcohol, yeast, citric acid & organic acids), soya oil, emulsifier, mould inhibitor and flavours.

Typical analysis (as fed basis):

Dry Matter	64%
ME	7.0 MJ/kg
Crude Protein	13%
Sugars (as sucrose)	14%
Fibre	Nil
Oil	2.0%
Ash	14%
Calcium	0.5%
Magnesium	0.4%
Phosphorus	0.07%
Potassium	3.5%
Sodium	0.2%

Physical Properties:

Specific Gravity	1.3
Viscosity (cp at 20°C)	60-300
pH	5.0
Litres/tonne	752
Gallons/tonne	165

Appearance: Dark brown syrupy liquid

Storage: Can be safely stored in vented waterproof tanks for up to 6 months.

Key Benefits:

- ✓ Cost-effective alternative to fats coating to reduce dust
- ✓ Highly palatable
- ✓ Absorbed rapidly into pellets
- ✓ Enhances visual appearance of pellets
- ✓ Excellent handling characteristics

Delivery: Pellacoat is available in bulk deliveries nationwide, ranging from 10 up to 28 tonnes.



Contact:

Premier Molasses Co. Ltd.,

Harbour Road, Foynes, Co. Limerick.

Deepwater Berth, Ringaskiddy, Co. Cork.

t: 069 65311 f: 069 65537 e: info@premiermolasses.ie

